



EAC



The HMi 470-Z1



Ultra Rugged
Driller's Display



ATEX, IECEX, AEX, CSA
& EAC Certified



High bright LCD panel

A precision-machined aluminum enclosure provides durability and low weight. Multi-touch and glove friendly touchscreen, field-tested and proven to perform in the harshest environments.

hmielements.com



Scan me to
find out more

The HMi 470-Z1



Certification

Certified to ATEX, IECEx, AEx (NEC505) Section 18 CSA 22,2 EAC.




Lightweight

Weighing in at 33lb/15kg.
W 385 x H 260 x D 116mm; 15.2 x 10.2 x 4.6 inches



Crisp & Bright Display

Sunlight readable PCT display.



Versatile Mounting options

Choice of mounting & connector options Yoke, VESA and Panel mounting. Rear or bottom mounted connectors.

PRODUCT TYPE	PC Workstation / Driller's Display Unit (DDU)
MODEL NO	470-Z1
TYPICAL EX CODE	ATEX: Ex e ib mb [ib] IIC T4 Gb, Ex tb [ibD] IIIC T135°C Db IECEx: Ex e ib mb [ib] IIC T4 Gb, Ex tb [ibD] IIIC T135°C Db USA: Class I, Zone 1, AEx e ib mb [ib] IIC T4, Class II, Zone 21, AEx tb [ib] IIIC T135°C Canada: Ex e ib m [ib] IIC T4 Gb, Ex t [idD] IIIC T135°C Db
DISPLAY SIZE	12.1" LCD panel with LED backlight display
DISPLAY TYPE	Projected Capacitive Technology (PCT) - Multi Touch, Glove Friendly
RESOLUTION	1024 x 768
PROCESSOR	Quad Core N Series 1.83GHz
OPERATING SYSTEM	Windows 10 Enterprise LTSB, Windows 7 Professional
STORAGE	64Gb, 128Gb & 256Gb
MEMORY	8Gb DDR3 SDRAM
ETHERNET OPTIONS	(optional) Copper Ethernet port 10/100/1000 Mbps/s Base-T (optional) Fibre Optic port via 850nm or 1310nm
WI-FI / BLUETOOTH	2.4 GHz Wi-Fi (802.11 b/g/n) Bluetooth V2
KEYBOARD / MOUSE	(optional) Intrinsically Safe PS/2 Interface
USB	Internal USB port for Safe area (optional) External USB type 2.0 port via ROTA DR4 connector
INGRESS PROTECTION	IP66 / NEMA4X
OPERATING TEMPERATURE	-40°C to +60°C (-40°F to +140°F)
STORAGE TEMP	-40°C to +80°C (-40°F to +176°F)
HUMIDITY	10 to 90 % non-condensing, operating 0 to 100 % non-operating
WEIGHT	< 33lbs / 15kg
DIMENSIONS	W 385 x H 260 x D 116mm; 15.2 x 10.2 x 4.6 inches
SHOCK & VIBRATION	Shock: In accordance with BS EN60068-2-27:2009 Vibration: In accordance with BS. EN60068-2-6:2008

United Kingdom

HMi Elements Ltd
Unit A & B, Windmill Industrial Estate,
Showfield Lane, Malton, UK, YO17 6BT
T +44 (0) 1653 699 908

United States

HMi Elements Inc
10900 Brittmoore Park Drive, Suite I,
Houston, TX 77041, USA
T +1 (0) 281 674-7815

Design and specifications subject to change without notice.
Errors and omission excepted

hmielements.com

